



every solution is **unique.**

R1000 Platform

Refrigerated Water Recirculating Systems

R1000 platform

	with air cooled condenser	with water cooled condenser
Cooling Capacity <small>(at 65°F/18°C supply water temp.)</small>	Watts 30,000 Btu/Hr 102,300	Watts 33,000 Btu/Hr 112,530
Compressor HP	10	10
Water Pump Capacity <small>alternatives available</small>	17 GPM (64.6 LPM)	17 GPM (64.6 LPM)
Pump Motor HP	2	2
Reservoir Volume	30 Gallons (114 Liters)	30 Gallons (114 Liters)
Power Requirements ¹ <small>alternatives available</small>	460V-3Ø-60Hz	460V-3Ø-60Hz
Dimensions (W x D x H)	119 x 91 x 168 cm 47 x 36 x 66 in.	76 x 91 x 142 cm 30 x 36 x 56 in.
Shipping Weight	1200 Lbs. (544 Kg)	900 Lbs. (408 Kg)

- Unit specifications will change by adding certain options.
- Cooling capacity of air-cooled units is based on 80°F/27°C ambient air temperature. Allowable ambient temperature range is 40°F to 100°F (4°C to 38°C). Changes in air temperature will affect cooling capacity. See Haskris Options (I) and/or (J) to operate outside this range.

¹ Also available in 50Hz—contact Haskris



Haskris Company
100 Kelly Street
Elk Grove Village, Illinois
60007 USA

Phone: 001-847-956-6420
Fax: 001-847-956-6595

Email: sales@haskris.com